



## Stainless Steel Braided Threaded Pump Connectors

### KEY FEATURES:

- Designed to absorb vibration in piping systems
- 321 or 316L stainless steel corrugated hose
- 304L stainless steel braid



### TC1: 321SS HOSE with 304SS BRAID and CARBON STEEL MALE NPT ENDS

SIZE	WP @70°F	P/N & MIN. LENGTH, (in.)		OTHER AVAILABLE LENGTHS and PART NUMBERS					
	(PSIG)	P/N	Length	10"	12"	18"	24"	36"	48"
1/4"	1647	TC1-004	6	TC1-004-160	TC1-004-192	TC1-004-288	TC1-004-384	TC1-004-576	TC1-004-768
3/8"	1639	TC1-006	6	TC1-006-160	TC1-006-192	TC1-006-288	TC1-006-384	TC1-006-576	TC1-006-768
1/2"	1200	TC1-008	6-1/2	TC1-008-160	TC1-008-192	TC1-008-288	TC1-008-384	TC1-008-576	TC1-008-768
3/4"	1034	TC1-012	7	TC1-012-160	TC1-012-192	TC1-012-288	TC1-012-384	TC1-012-576	TC1-012-768
1"	796	TC1-016	8	TC1-016-160	TC1-016-192	TC1-016-288	TC1-016-384	TC1-016-576	TC1-016-768
1-1/4"	600	TC1-020	8-1/2	TC1-020-160	TC1-020-192	TC1-020-288	TC1-020-384	TC1-020-576	TC1-020-768
1-1/2"	551	TC1-024	9	TC1-024-160	TC1-024-192	TC1-024-288	TC1-024-384	TC1-024-576	TC1-024-768
2"	557	TC1-032	10-1/2	TC1-032-160	TC1-032-192	TC1-032-288	TC1-032-384	TC1-032-576	TC1-032-768
2-1/2"	387	TC1-040	12		TC1-040-192	TC1-040-288	TC1-040-384	TC1-040-576	TC1-040-768
3"	316	TC1-048	14		TC1-048-192	TC1-048-288	TC1-048-384	TC1-048-576	TC1-048-768
4"	232	TC1-064	16		TC1-064-192	TC1-064-288	TC1-064-384	TC1-064-576	TC1-064-768

### TC2: 321SS HOSE with 304SS BRAID and 304SS MALE NPT ENDS

SIZE	WP @70°F	P/N & MIN. LENGTH, (in.)		OTHER AVAILABLE LENGTHS and PART NUMBERS					
	(PSIG)	P/N	Length	10"	12"	18"	24"	36"	48"
1/4"	1647	TC2-004	6	TC2-004-160	TC2-004-192	TC2-004-288	TC2-004-384	TC2-004-576	TC2-004-768
3/8"	1639	TC2-006	6	TC2-006-160	TC2-006-192	TC2-006-288	TC2-006-384	TC2-006-576	TC2-006-768
1/2"	1200	TC2-008	6-1/2	TC2-008-160	TC2-008-192	TC2-008-288	TC2-008-384	TC2-008-576	TC2-008-768
3/4"	1034	TC2-012	7	TC2-012-160	TC2-012-192	TC2-012-288	TC2-012-384	TC2-012-576	TC2-012-768
1"	796	TC2-016	8	TC2-016-160	TC2-016-192	TC2-016-288	TC2-016-384	TC2-016-576	TC2-016-768
1-1/4"	600	TC2-020	8-1/2	TC2-020-160	TC2-020-192	TC2-020-288	TC2-020-384	TC2-020-576	TC2-020-768
1-1/2"	551	TC2-024	9	TC2-024-160	TC2-024-192	TC2-024-288	TC2-024-384	TC2-024-576	TC2-024-768
2"	557	TC2-032	10-1/2	TC2-032-160	TC2-032-192	TC2-032-288	TC2-032-384	TC2-032-576	TC2-032-768
2-1/2"	387	TC2-040	12		TC2-040-192	TC2-040-288	TC2-040-384	TC2-040-576	TC2-040-768
3"	316	TC2-048	14		TC2-048-192	TC2-048-288	TC2-048-384	TC2-048-576	TC2-048-768
4"	232	TC2-064	16		TC2-064-192	TC2-064-288	TC2-064-384	TC2-064-576	TC2-064-768

### TC3: 316SS HOSE with 304SS BRAID and 316SS MALE NPT ENDS

SIZE	WP @70°F	P/N & MIN. LENGTH, (in.)		OTHER AVAILABLE LENGTHS and PART NUMBERS					
	(PSIG)	P/N	Length	10"	12"	18"	24"	36"	48"
1/4"	1647	TC3-004	6	TC3-004-160	TC3-004-192	TC3-004-288	TC3-004-384	TC3-004-576	TC3-004-768
3/8"	1639	TC3-006	6	TC3-006-160	TC3-006-192	TC3-006-288	TC3-006-384	TC3-006-576	TC3-006-768
1/2"	1200	TC3-008	6-1/2	TC3-008-160	TC3-008-192	TC3-008-288	TC3-008-384	TC3-008-576	TC3-008-768
3/4"	1034	TC3-012	7	TC3-012-160	TC3-012-192	TC3-012-288	TC3-012-384	TC3-012-576	TC3-012-768
1"	796	TC3-016	8	TC3-016-160	TC3-016-192	TC3-016-288	TC3-016-384	TC3-016-576	TC3-016-768
1-1/4"	600	TC3-020	8-1/2	TC3-020-160	TC3-020-192	TC3-020-288	TC3-020-384	TC3-020-576	TC3-020-768
1-1/2"	551	TC3-024	9	TC3-024-160	TC3-024-192	TC3-024-288	TC3-024-384	TC3-024-576	TC3-024-768
2"	557	TC3-032	10-1/2	TC3-032-160	TC3-032-192	TC3-032-288	TC3-032-384	TC3-032-576	TC3-032-768
2-1/2"	387	TC3-040	12		TC3-040-192	TC3-040-288	TC3-040-384	TC3-040-576	TC3-040-768
3"	316	TC3-048	14		TC3-048-192	TC3-048-288	TC3-048-384	TC3-048-576	TC3-048-768
4"	232	TC3-064	16		TC3-064-192	TC3-064-288	TC3-064-384	TC3-064-576	TC3-064-768

\* Consult Penflex products catalog for further details on design, installation and use, temperature adjustment factors, and other technical specifications.