



Stainless Steel Braided Flanged Pump Connectors

KEY FEATURES:

- Designed to absorb vibration in piping systems
- 321 or 316L stainless steel corrugated hose
- 304L or 316L stainless steel braid
- ASTM A36 Carbon Steel Class 150 Slip-on Plate Flanges



| Size (mm) | Part number | Overall Length (mm) | Working Pressure @21°C (BAR)* | Flange Thickness (mm) | Approx. Weight per Meter (Kg) |
|-----------|-------------|---------------------|-------------------------------|-----------------------|-------------------------------|
| 50 | PFPC-032 | 229 | 32.75 | 15.88 | 16.37 |
| 65 | PFPC-040 | 229 | 24.13 | 15.88 | 20.83 |
| 80 | PFPC-048 | 229 | 20.68 | 15.88 | 22.32 |
| 100 | PFPC-064 | 229 | 17.24 | 15.88 | 29.76 |
| 125 | PFPC-080 | 279 | 12.07 | 19.05 | 41.67 |
| 150 | PFPC-096 | 279 | 11.38 | 19.05 | 49.11 |
| 200 | PFPC-128 | 305 | 16.13 | 25.40 | 77.38 |
| 250 | PFPC-160 | 330 | 15.86 | 25.40 | 110.12 |
| 300 | PFPC-192 | 356 | 11.10 | 25.40 | 148.82 |

- Sizes 50 - 150 supplied with plain weave braid.
- Sizes 200 - 300 supplied with braided braid to allow for higher Working Pressure and braid coverage.
- See Penflex products catalog for hose dimensions and braid constructions.
- Consult Penflex products catalog for further details on design, installation and use, temperature adjustment factors, and other technical specifications.

