



IE30 Interlocked Exhaust Hose

Strip Thickness 0.010/0.012"

| NOMINAL DIAMETERS | | MINIMUM COILING DIAMETER | Wt/Ft |
|-------------------|---------|--------------------------|-------|
| INSIDE | OUTSIDE | | |
| ½ | 0.61 | 6 | 0.23 |
| ¾ | 0.834 | 7 | 0.32 |
| 1 | 1.11 | 9 | 0.41 |
| 1 ¼ | 1.385 | 11 | 0.44 |
| 1 ½ | 1.61 | 13 | 0.54 |
| 1 ¾ | 1.86 | 15 | 0.63 |
| 2 | 2.11 | 17 | 0.72 |
| 2 ¼ | 2.36 | 19 | 0.80 |
| 2 3/8 | 2.540 | 20 | 0.85 |
| 2 ½ | 2.61 | 21 | 0.89 |
| 2 ¾ | 2.86 | 23 | 0.96 |
| 2 7/8 | 3.083 | 25 | 1.00 |
| 3 | 3.11 | 26 | 1.06 |
| 3 ½ | 3.61 | 30 | 1.24 |
| 4 | 4.200 | 34 | 1.41 |
| 5 | 5.215 | 42 | 1.76 |
| 5 1/2 | 5.700 | 46 | 1.94 |
| 6 | 6.11 | 50 | 2.11 |
| 7 | 7.11 | 58 | 2.46 |
| 8 | 8.11 | 66 | 2.80 |

IE50 Interlocked Exhaust Hose

Strip Thickness 0.018/0.020"

| NOMINAL DIAMETERS | | MINIMUM COILING DIAMETER | Wt/Ft |
|-------------------|---------|--------------------------|-------|
| INSIDE | OUTSIDE | | |
| 1 | 1.22 | 17 | 0.70 |
| 1 ½ | 1.66 | 17 | 0.86 |
| 1 ¾ | 1.91 | 19 | 1.00 |
| 2 | 2.20 | 22 | 1.13 |
| 2 ¼ | 2.495 | 25 | 1.27 |
| 2 ½ | 2.66 | 27 | 1.40 |
| 2 ¾ | 2.91 | 29 | 1.54 |
| 3 | 3.16 | 32 | 1.67 |
| 3 ½ | 3.66 | 38 | 1.95 |
| 4 | 4.230 | 43 | 2.22 |
| 5 | 5.16 | 53 | 2.76 |
| 6 | 6.16 | 63 | 3.30 |
| 7 | 7.16 | 74 | 3.85 |
| 8 | 8.16 | 84 | 4.39 |

NOTES

1. Tabulated weights apply to stainless steel.
2. Intermediate sizes, alloys and flexibility characteristics are all subject to quotation from the factory.
3. Dimensional Tolerance is +/- .020"